



PORTABLE MAGNETIC DRILLS

		HMD115	HMD150	HMD904	HMD905	HMD927	HMD917	HMD505 / HMD508	HMD933
		Low Profile		Fabricating				Heavy Duty Drilling	
Annular Cutters	RotaLoc™	✓	✓	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	
	RotaLoc Plus™		✓	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	
	"12,000-Series"			✓	✓	✓	✓	✓	With Adapter (5/8" & Larger)
	Copperhead™ Carbide Tipped			✓	✓	✓	✓	✓	
	"42/43,000-Series"								✓
Model Specifications	Diameter Min./Max.	1/2" to 1-1/16" (12 - 27mm)	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 2-3/8" (12 - 60mm)	7/16" to 2-3/8" (12 - 60mm)	5/8" to 3-1/16" (16 - 77mm)
	Depth Max.	3/4" (19mm)	1" (25mm)	2" (50mm)	2" (50mm)	2" (50mm)	3" (76mm)	3" (76mm)	3" (76mm)
	Cutter Mounting	Bayonet Style	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" or 1-1/4" Weldon Shank
	No-Load R.P.M.	450	450	450	250 / 450	250 / 450	250 / 450	250 / 450 450 / 750	70/120 200/332
	Model Weight	21.3 lbs (9.7 kg)	22.7 lbs (10.3 kg)	28.9 lbs (13.1 kg)	35 lbs (15.9 kg)	43 lbs (19.5 kg)	46 lbs (20.9 kg)	45 lbs (20.4 kg)	72 lbs (32.6 kg)
	Thru-the-Tool Coolant			✓	✓	✓	✓	✓	✓
Available Accessories	Carrying Case Included	✓	✓	✓	✓		✓	✓	
	Swivel Base			Optional	Optional	Optional	Optional		
	Pipe Adapter			✓	✓	Manual Mode	✓	✓	Bracket Mount
	Tap Attachment			✓	✓	Manual Mode	✓		
	Vac-Pad™			✓	✓				
	Coolant Bottle			Optional	Included	Included	Included	Included	Included
	Countersink Kit			✓	✓	Manual Mode	✓	✓	With Adapter
	Twist Drill Adapter			✓	✓	Manual Mode	✓	✓	With Adapter
	Ratchet Drive	✓	✓	✓	✓			✓	
	Arbor Extender			✓	✓	Manual Mode	✓	✓	With Adapter
	Drill Chuck			✓	✓	Manual Mode	✓		
	RotaLoc™ Spindle Adapter			✓	✓	Manual Mode	✓	✓	